

FLAT TOP WELL LIGHT 120V

55702BZ-LMA27K

VARIABLE OUTPUT LED 2700K WELL LIGHT
120V



DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	4"
DEPTH:	4.5
WEIGHT:	3lb

LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
LED NAME:	27G4SE-120V
WATTAGE:	12w, 8w, 5w, 3w LED *Included
VOLTAGE:	120v
COLOR TEMP:	2700
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	NO

MOUNTING	
LEAD WIRE:	1 X 96"

SHIPPING	
CARTON LENGTH:	23.5
CARTON WIDTH:	7.5
CARTON HEIGHT:	5
CARTON WEIGHT:	2.5



PRODUCT DETAILS:

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Optimal drive-over protection up to 4,500 lbs
- PVC constructed concrete pour kit and burial sleeve is supplied.
- Optional performance lenses available