



WS-W18122

	Project:	
	Location:	
-		

Fixture Type:

Catalog Number:



Mako

WS-W18122

PRODUCT DESCRIPTION

Sleek and striking. Modern lighting designed at just the right angle. This low-profile wall sconce projects a blade of light on the wall behind to feature its own silhouette and asecond blade cast downward to light the path below. Defined by an angular upright, Mako enhances both interior and exterior locations as a wet listed, ADA Compliant architectural luminaire. Customize your color temperature from three choices.

FEATURES

- \bullet Driver concealed within the canopy
- Down and indirect illumination
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K

SPECIFICATIONS

Rated Life	50000 Hours
Standards	ETL, cETL,Wet Location Listed
Input	120/277V
Dimming	TRIAC: 100-10%
Mounting	Can be mounted on wall vertically or upside down
Color Temp	3000K,3500K,4000K
CRI	90
Construction	Extruded aluminum body with white silk screen glass

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W18122 22"	3000K	AL Brushed Aluminum	16.7W	1500	364
	3000K	BK Black	16.7W	1500	364
	3500K	AL Brushed Aluminum	16.7W	1500	434
	3500K	BK Black	16.7W	1500	434
	4000K	AL Brushed Aluminum	16.7W	1500	410
	4000K	BK Black	16.7W	1500	410

Example: WS-W18122-40-BK