

Project:

ALC LED Sconce Spec Sheet

SKU: 3050.13-SN25 Learn more at: https://sonnemanlight.com/alc-led-pendant

Description: A classic modern architectural lighting form, Architectural Lighting Cylinders are available in a <u>surface mount</u> configuration as well as a <u>sconce</u> and pendant in a variety of sizes and finishes, with multiple beam spread options and a number of glass and metal trims.

Type #:




25 Narrow

Flood Lens

Aluminum





Dimensions

Height: 8.25" Extends: 3.5" 3.5 Minimum Extension: Maximum Extension: 3.5 2" Diameter: 4.5" Canopy/Backplate/Base: Shape: Snoot Trim Size: 2" One-Sided Canopy/Backplate/Base Depth: 0.5

Installation

Shade

Lens Type:

Shade 1 Material:

Installation:

Licensed electrician required
Installation Orientation:

Any Orientation

General Listings

Features: Damp Rated
Certification: C-ETL-US
Color/Finish: Satin Nickel
(.13)
Dark Sky Friendly: N

Electrical Specs

Bulb(s) Included?: Yes Bulb 1 Type: Integral LED **Bulb Quantity:** Input Voltage: 120VAC Wattage: 10 Initial Lumens: 1060 **Delivered Lumens:** 800 3000K Color Temperature: CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: **Outlet Box** TRIAC/ELV Dimming Type: Bulb Max Wattage: 10

Available Finishes

Available Finishes: Satin Nickel w/Bezel Trim, Satin Nickel w/Etched Glass Trim, Satin Nickel w/Etched Ribbon Glass Trim, Satin Nickel w/Snoot Trim