ACE HEAD

PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- Efficient, classic adjustable spot head design
- Adjustable spot head design and variable stem length options available
- Fully dimmable integrated LED lamp
- Idea for residential and commercial lighting applications
- Monopoint version The LED Driver is housed within the junction box. (L. 3.05" | W. 1.5" | H. .98")



LAMPING

Includes 12 volt 9.4 watt, 518.5 delivered lumens, 2700K or 3000K, LED module. Dimmable with most LED compatible or ELV and Triac dimmers. Ace head can pivot 90° (horizontal to straight down). Integrated lens holder accommodates up to (2) lenses and louvers (sold separately). As a general rule when using the Ace head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support. Ace head only compatible with AC transformers. Compatible with MOCGG, MOCSF, MOCLL, MOCEC, MOCLSI AND MOC LSI2 lenses.





ORDERING INFORMATION

700	SYSTEM	ACE	CRI	COLOR TEMP	BEAM SPREAD	LENGTH (A)	FINISH
	FJ FREEJACK		9 90 CRI	27 2700K	40 40°	55"	Z ANTIQUE BRONZE
	MP MONOPOINT			30 3000K			BR PLATED BRASS
	MO MONORAIL						S SATIN NICKEL

Note. Note. MP includes 4" Round Flush Canopy. For custom stem lengths, please contact the Quotes Department.

700	ACE		
JOB NAME			
NOTES			




© 2019 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification. 7400 Linder Avenue, Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 | techlighting.com

ACE HEAD

VISUAL COMFORT & CO.

SPECIFICATIONS

PRIMARY MATERIAL	Metal	
SHADE MATERIAL	Metal	
NET WEIGHT	1.5 lbs	
HEIGHT	1.9in	
WIDTH	1.9in	
LENGTH	3.6in	
BEAM SPREAD		
UP LIGHT / DOWN LIGHT / BOTH?		
WET LISTED		
DAMP LISTED		
DRY LISTED		
MIN. HANGING HEIGHT	5in	
MAX HANGING HEIGHT	5in	
TOTAL CORD LENGTH		
SLOPED CEILING ADAPTABLE?	No	
GENERAL LISTING	ETL Listed	
INCLUDES		



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		518.5		
WATTS		9.4		
MAX WATTAGE PER BULB		9.4W		
		12V ELV, TRIAC		
		120V ELV, TRIAC		
ССТ		2700K		
		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

* Dimming information available at <u>www.techlighting.com/Downloads#dimming</u> ** Visit techlighting.com for specific warranty limitations and details.

T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



© 2019 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.