PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- · Hand-blown by skilled European artisans
- · Contemporary version of the classic cylinder pendant
- Complementary Manette low-voltage and Manette ceiling fixture available by Tech Lighting
- Ships with 16-feet of field-cuttable cord
- Monopoint version The LED Driver is housed within the junction box. (L. 3.05" | W. 1.5" | H. .98")



Includes 6 watt, 378 delivered lumens 80 CRI 3000K, LED. Dimmable with most LED compatible ELV or Triac dimmers. Ships with 16 feet of field cuttable suspension cable.



Clear / Clear Black Ring



ORDERING INFORMATION

700	SYSTEM MAN	COLOR	@HEADERCOLOR2LABEL	FINISH	LAMP
	FJ FREEJACK MP MONOPOINT MO MONORAIL	CL CLEAR TK TRANSPARENT SMOKE	CLCLEAR TK TRANSPARENT SMOKE	ZZ ANTIQUE BRONZE/ANTIQUE BRONZE BS BLACK/SATIN NICKEL SS SATIN NICKEL/SATIN NICKEL	-LED 12 VOLT LED 3000K

Note: MP includes 4" Round Flush Canopy.


700 JOB NAME	MAN	 	
NOTES			



MANETTE PENDANT

SPECIFICATIONS

Glass
3.1 lbs
13.3in
3.5in
3.5in
19.8in
85.8in
Yes 45° Max
ETL Listed



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	378			
WATTS	6			
MAX WATTAGE PER BULB	6W			
	12V ELV, MLV 120V ELV, MLV			
ССТ	3000K			
CRI	90 CRI			
LED LIFETIME				
L70	>50000			
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE	Integrated LED			
LAMP SHAPE	Integrated LED			
LAMP INCLUDED?	True			
WARRANTY**	5 Years			

^{*} Dimming information available at www.techlighting.com/Downloads#dimming ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6/JA8.		No	
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.		N/A	

 $^{^{*}}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

