An architectural profile reminiscent of beautifully classic roof lines delivers significant light output in this modern LED wall sconce suitable for both indoor and outdoor applications. The Pitch Single's die-cast metal body houses powerful LED light sources that create visual appeal as light cascades down along a wall.

High quality LM80-tested LEDs

for consistent long-life performance and color

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

Can be mounted for up lighting or down lighting

SPECIFICATIONS

DELIVERED LUMENS822.6WATTS26.1VOLTAGE120V, 277VDIMMINGELVLIGHT DISTRIBUTIONSymmetricMOUNTING OPTIONSDownlight or UplightCCT2700K, 3000KCRI80+
VOLTAGE120V, 277VDIMMINGELVLIGHT DISTRIBUTIONSymmetricMOUNTING OPTIONSDownlight or UplightCCT2700K, 3000K
DIMMING ELV LIGHT DISTRIBUTION Symmetric MOUNTING OPTIONS Downlight or Uplight CCT 2700K, 3000K
LIGHT DISTRIBUTION Symmetric MOUNTING OPTIONS Downlight or Uplight CCT 2700K, 3000K
MOUNTING OPTIONS Downlight or Uplight CCT 2700K, 3000K
ССТ 2700К, 3000К
CRI 80+
COLOR BINNING 3 Step
BUG RATING B1-U0-G0
DARK SKY Compliant (Downlight)
WET LISTED IP65
GENERAL LISTING ETL
Can be used to comply with CEC 2016 Title 24 CALIFORNIA TITLE 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP -30°C
FIELD SERVICEABLE LED No
CONSTRUCTION Aluminum
HARDWARE Stainless Steel
FINISH Powder Coat
LED LIFETIME L70; 70,000 Hours
WARRANTY* 5 Years
WEIGHT 1.2 lbs.



PITCH SINGLE shown in black



PITCH SINGLE shown in charcoal



PITCH SINGLE shown in bronze




PITCH SINGLE shown in silver

* Visit techlighting.com for specific warranty limitations and details.

ORDERING INFORMATION


700WSPIT	SIZE	FINISH	LAMP	
	S SINGLE	B BLACKB BRONZECHARCOALSILVER	-LED827277 -LED830	LED 80 CRI, 2700K 120V LED 80 CRI, 2700K 277V LED 80 CRI, 3000K 120V LED 80 CRI, 3000K 277V



PHOTOMETRICS*

PITCH SINGLE

Total Lumen Output:	822.6
Total Power:	26.2
Luminaire Efficacy:	31.4
Color Temp:	3000K
CRI:	80+
BUG Rating:	B1-U0-G0



PROJECT INFO

FIXTURE TYPE & QUANTITY

(II)

JOB NAME & INFO

 \otimes 2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

NOTES

TECH LIGHTING

VISUAL COMFORT & CO.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

*For latest photometrics, please visit www. techlighting.com/OUTDOOR