

The contemporary aesthetic of the Blade 18 outdoor wall sconce creates soft indirect, reduced-glare illumination by aiming light back against the wall for accenting architecture as well as for wayfinding. Available in two sizes, 18" and 24" and two finishes.

- **Selectable CCT (2700K/3000K)**
- **Universal 120V-227V**
- **Outstanding protection against the elements:**
  - Wet Listed IP65 Rated
  - Stainless Steel Mounting Hardware
  - Powder Coat Finishes

## SPECIFICATIONS

DELIVERED LUMENS	1105
WATTS	20.33
VOLTAGE	Universal 120V-277V
DIMMING	Dimmable with most LED compatible ELV & TRIAC dimmers + 0-10V
LIGHT DISTRIBUTION	Symmetric
OPTICS	not applicable
MOUNTING OPTIONS	Wall
CCT	2700K/3000K Selectable
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B0-U3-G0
DARK SKY	Non Compliant
WET LISTED	IP65
GENERAL LISTING	ETL, ADA
CALIFORNIA TITLE 24	Can be used to comply with CEC 2019 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	No
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; >60,000 Hours
WARRANTY*	5 Years
WEIGHT	1.5 lbs.

\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.




BLADE 18 OUTDOOR WALL  
shown in black

BLADE 18 OUTDOOR WALL  
shown in bronze

## ORDERING INFORMATION

PRODUCT	CRI/CCT	LENGTH	FINISH	VOLTAGE
7000WBLD	92730 90 CRI 2700K/3000K SELECTABLE	18 18"	B BLACK Z BRONZE	UNV 120V-277V



Blade 18 Outdoor Wall

## PROJECT INFO

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES

