VETRA FLUSH

TECH LIGHTING

PRODUCT FEATURES

- Inspired by textiles, hand-blown glass flushmount features linen weave design
- Recommended lamping is 2 medium based bulbs with 60w maximum each (purchased separately). or can be ordered with optional 6.5 watt LED STI9 bulbs for enhanced energy efficiency
- Fully dimmable with most dimmers to create just the right atmosphere
- Linen weave design silk screened on hand-blown glass shade, creates a textured surface through which the light softly glows
- Lamp sockets with satin nickel finish complete the look
- Protected by a 1-year warranty.



LAMPING

Available with or without lamp. (2) E26 medium base sockets 60w max. LED version includes (2) 3.5 watt 465 total delivered lumens 90CRI 2700K LED STI9. Dimmable with a low-voltage electronic dimmer. 120v.

Linen



Linen

ORDERING INFORMATION

| 700FMVTR COLOR | FINISH | LAMP | |
|----------------|----------------|-------------------------------|--|
| LN LINEN | S SATIN NICKEL | NO LAMP | |
| | | -LED927 LED 90 CRI 2700K 120V | |
| | | | |

700FMVTR JOB NAME NOTES

Ð.


© 2019 Tech Lighting, LLC. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, LLC. Tech Lighting reserves the right to change specifications for product improvements without notification. 7400 Linder Avenue, Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 | techlighting.com

VETRA FLUSH

TECH LIGHTING

SPECIFICATIONS

| HARDWARE MATERIAL | Metal |
|-------------------------------|------------|
| SHADE MATERIAL | Glass |
| NET WEIGHT | 7 lbs |
| HEIGHT | 6in |
| WIDTH | 13in |
| LENGTH | 13in |
| UP LIGHT / DOWN LIGHT / BOTH? | |
| WET LISTED | |
| DAMP LISTED | Yes |
| DRY LISTED | |
| WALL / CEILING MOUNT | |
| GENERAL LISTING | ETL Listed |
| INCLUDES | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------|-----------------|----------------|---------|-----------------|
| DELIVERED LUMENS | 465 | | | |
| WATTS | 3.5 | | | |
| MAX WATTAGE PER BULB | 120W | | | 120W |
| INPUT VOLTAGE | 120V | | | 120V |
| DIMMING TYPE* | ELV, TRIAC | | | ELV, TRIAC |
| CCT | 2700K | | | |
| CRI | 90 CRI | | | |
| ED LIFETIME | | | | |
| .70 | 25000 | | | |
| VERAGE BULB HOURS | 25000 | | | |
| FIELD SERVICEABLE LED | | | | |
| _AMP BASE | E26 Medium Base | | | E26 Medium Base |
| _AMP SHAPE | T6 | | | T6 |
| AMP INCLUDED? | Y | | | Ν |
| WARRANTY** | 1 Year | | | 1 Year |

* Dimming information available at <u>www.techlighting.com/Downloads#dimming</u> ** Visit techlighting.com for specific warranty limitations and details.

T20/T24 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|---|-------------------|-------------------------|--------------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6. | | Yes | N/A |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. | l | No | N/A |

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



© 2019 Tech Lighting, LLC. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, LLC. Tech Lighting reserves the right to change specifications for product improvements without notification.