

Strada Large Flush Mount

Item **#** KW 4071

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):


Phillips Screwdriver	Slotted Screwdriver	Measuring Tape
Wire Cutters	Wire Strippers	

- 1. Carefully remove all parts from the box. Place on a clean, soft surface.
- 2. Remove mounting plate (B) from fixture body (E) by removing branch (H), hex nut (I) and branch (J) using provided wrench (L).
- 3. Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)**.
- 4. Attach branchs (G) to fixture body (E) and secure with hex nuts using provided wrench (K).
- 5. Attach branchs (F) to fixture body (E) and secure with hex nuts using provided wrench (K1).
- 6. Install light bulbs into the sockets.
- Run support cable through hole on back of mounting plate (B). Loosen cable lock and install to end of support cable. Insert other end of cable through the cable lock and tighten ends with a screwdriver to secure. (see diagram 1)
- Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 2). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut (A).

NOTE: It is imperative that the fixture is grounded.

9. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut **(A)**.

Visual Comfort



Strada Large Flush Mount

Item # KW 4071

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

10. Connect fixture hot wire (black) to the supply hot wire (usually black) using the wire nut **(A)**.

CAUTION: Do not reverse the hot and neutral connections.

- 11. Make sure all wire connections are tight and tuck into the junction box.
- 12. Attach fixtureto threaded nipple (**D**) and secure with branch (**H**) and hex nut (**I**) using provided wrench (**L**).
- 13. Thread branch (J) to the bottom of threaded nipple (D).

Care Instructions: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.

VISUAL COMFORT



Strada Large Flush Mount

Item # KW 4071

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

For a more personalized style you are able to gently bend spines in any direction.

NOTICE: BENDING SPINES MULITPLE TIMES CAN CAUSE THEM TO BREAK.

VISUAL COMFORT

