ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

ITEM NO: DJ42000 NAME: Gaetano Chandelier

MATERIAL TYPE: Brass FINISH: Vintage Brass

SOCKET TYPE: E12 SOCKET QTY: 8

BULB WATTAGE: 25W/CFL 7W/LED 5W

VOLTAGE: 110-120V ITEM NET WEIGHT: 15.5LBS



TO ASSEMBLE:

- Shut off the main electrical supply from the main fuse box/circuit breaker and unpack all fixture parts and hardware.
- Included are (1) 3", (1) 6" pipe and (2) 12" pipes. At least (1) 6" pipe must be used. Pass the attached electric cable through the desired amount of pipes, keeping the threaded part of the pipes toward the ceiling.
- Screw pipes starting with the one closest to the Main Body and moving upwards to the canopy. Tighten the allen screws using included allen wrench.
- Gently pull wiring down from ceiling junction box and allow to hang and remove mounting plate from the canopy by unscrewing the collar.
- 5. Carefully inspect the pendant's fixture wires.

 Neutral fixture wire: White

 Hot fixture wire: Black

 Ground wire: Green
- 6. Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
- Attach the neutral fixture wire from the pendant to the neutral junctionbox wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.
- Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten each together with a wire nut and wrap the connection with electrical tape. DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
- Gently tuck the wire connections neatly into the ceiling junction box and place the mounting plate over the center of the ceiling junction box.
- 10. Align holes in mounting plate with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head screwdriver. Push canopy up over the mounting plate until it is flush with the ceiling.
- 11. Push collar through hole in canopy and thread onto nipple on the mounting plate. Secure by turning collar clockwise until

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.

PARTS INCLUDED:

Mounting Plate	Qty: 1	
Body	Qty: 1	
Canopy	Qty: 1	
Pipe	Qty: 4	

HARDWARE INCLUDED:

Mounting Screws	2	Allen Screws	2	
Plastic Wire Connector	2	Allen Wrench	1	
Green Ground Screw	1			

TO INSTALL YOU WILL NEED:

- 2 people recommended
- Phillips Screwdriver

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation of this chandelier.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.

For customer service questions call 1-800-338-2150

ARTERIORS