ASSEMBLY INSTRUCTIONS	
ITEM DESCRIPTION:	
ITEM NO: DJ42004 NAME: Pavo Large Pendant	
MATERIAL TYPE: Wood FINISH: Dark Walnut	
SOCKET TYPE: E26 SOCKET QTY: 4	
BULB WATTAGE: 40W/CFL 10W/LED 9W	V
VOLTAGE: 110-120V ITEM NET WEIGHT: 10LBS	
	TO ASSEMBLE:
	1. Shut off the main electrical supply from the main fuse
	box/circuit breaker and unpack all fixture parts and hardware.
	 Gently pull wiring down from ceiling junction box and allow to hang and remove mounting plate from the canopy by unscrewing the collar.
	3. Carefully inspect the pendant's fixture wires.
	Neutral fixture wire: White Hot fixture wire: Black
	Ground wire: Green
	 Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
	5. Attach the neutral fixture wire from the pendant to the neutral
PARTS INCLUDED:	junctionbox wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.
Mounting Plate	 Attach the hot fixture wire from the pendant to the hot junction
Сапору	box wire (usually black). Fasten each together with a wire nut
Pipe	and wrap the connection with electrical tape. DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
	 Gently tuck the wire connections neatly into the ceiling junction box.
	 Place the mounting plate over the center of the ceiling junction box.
	9. Align holes in mounting plate with holes in junction box and
	attach with two mounting bolts. Secure bolts with a Phillips head screwdriver.
HARDWARE INCLUDED:	10. Push canopy up over the mounting plate until it is flush with
Mounting Screws Canopy Screws	the ceiling.
Plastic Wire Connector Hexangular Screw	11. Push collar through hole in canopy and thread onto nipple on the mounting plate. Secure by turning collar clockwise until
Green Ground Screw Allen Wrench	canopy is flush with the ceiling.
TO INSTALL YOU WILL NEED:	12. Restore power to junction box and test fixture. Insert 25-Watt
2 people recommended Phillips Screwdriver	maximum E26 Type A bulb into fixture. DO NOT EXCEED SPECIFIED WATTAGE OF FIXTURE.
These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation	
of this chandelier.	CARE INSTRUCTIONS:
We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.	Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.
For customer service questions call 1-800-338-2150	ARTERIORS