ASSEMBLY INSTRUCTIONS	
	3
ITEM DESCRIPTION:	
ITEM NO: DK42043 NAME: Chainmail Pendant	
MATERIAL TYPE: Brass FINISH: Antique Brass	And and a second se
SOCKET TYPE: E12 SOCKET QTY: 3	10000000000000000000000000000000000000
BULB WATTAGE: 25W/CFL 7W/LED 5W	
VOLTAGE: 110-120V ITEM NET WEIGHT: 12LBS	
	TO ASSEMBLE: 1. Shut off the main electrical supply from the main fuse box/circuit breaker and unpack all fixture parts and hardware. 2. Conthe pull wiking down from colling invotion has and allow.
	 Gently pull wiring down from ceiling junction box and allow to hang and remove mounting plate from the canopy by unscrewing the collar.
	3. Carefully inspect the pendant's fixture wires. Neutral fixture wire: White Hot fixture wire: Black Ground wire: Green
	 Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
PARTS INCLUDED:	 Attach the neutral fixture wire from the pendant to the neutral junctionbox wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.
Mounting Plate Qty: 1 Canopy Qty: 1 Body Qty: 3	6. Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten each together with a wire nut and wrap the connection with electrical tape. DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
Qty: 4	Gently tuck the wire connections neatly into the ceiling junction box and place the mounting plate over the center of the ceiling junction box.
	 Align holes in mounting plate with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head screwdriver. Push canopy up over the mounting plate until it is flush with the ceiling.
HARDWARE INCLUDED:	10. Push collar through hole in canopy and thread onto nipple on
Mounting Screws 2	the mounting plate. Secure by turning collar clockwise until canopy is flush with the ceiling.
Plastic Wire Connector 2	11. Restore power to junction box and test fixture. Insert 25-Watt
Green Ground Screw 1	maximum E12 Type B bulb into fixture. DO NOT EXCEED SPECIFIED WATTAGE OF FIXTURE.
TO INSTALL YOU WILL NEED: • 2 people recommended • Phillips Screwdriver	
These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation of this chandelier.	CARE INSTRUCTIONS:
We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.	Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.
For customer service questions call 1-800-338-2150	ARTERIORS