ASSEMBLY INSTRUCTIONS	
ITEM DESCRIPTION:	
ITEM NO: DK42047 NAME: Ice Large Pendant	
MATERIAL TYPE: Glass FINISH: Clear	gg 🛍 🔤
SOCKET TYPE: E26 SOCKET QTY: 1	
BULB WATTAGE: 40W/CFL 10W/LED 9W	
VOLTAGE: 110-120V ITEM NET WEIGHT: 7LBS	
	TO ASSEMBLE:
	<ol> <li>Shut off the main electrical supply from the main fuse box/circuit breaker and unpack all fixture parts and hardware.</li> </ol>
	<ol><li>Gently pull wiring down from ceiling junction box and allow to hang and remove mounting plate from the canopy by</li></ol>
	unscrewing the collar.
	<ol> <li>Carefully inspect the pendant's fixture wires.</li> <li>Neutral fixture wire: White</li> </ol>
	Hot fixture wire: Black
	Ground wire: Green
	<ol> <li>Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.</li> </ol>
PARTS INCLUDED:	5. Attach the neutral fixture wire from the pendant to the neutral
Mounting Plate Qty: 1	<ul> <li>junctionbox wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.</li> </ul>
Canopy Qty: 1	<ol> <li>Attach the hot fixture wire from the pendant to the hot junction</li> </ol>
Loop Qty: 1	box wire (usually black). Fasten each together with a wire nut
Socket Assembly Qty: 1	and wrap the connection with electrical tape. DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
	7. Gently tuck the wire connections neatly into the ceiling
	junction box and place the mounting plate over the center of the
	ceiling junction box.
	<ol> <li>Align holes in mounting plate with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head</li> </ol>
	screwdriver. Push canopy up over the mounting plate until it is flush with the ceiling.
HARDWARE INCLUDED:	
Mounting Screws 2 Canopy Screws 4 Plactic Wire Connector 2 Allen Screw 1	<ol> <li>Push collar through hole in canopy and thread onto nipple on the mounting plate. Secure by turning collar clockwise until canopy is flush with the ceiling.</li> <li>Restore power to junction box and test fixture. Insert 40-Watt maximum E26 Type T10 bulb into fixture. DO NOT EXCEED SPECIFIED</li> </ol>
Plastic Wire Connector         2         Allen Screw         1           Green Ground Screw         1         Allen Wrench         1	
TO INSTALL YOU WILL NEED: • 2 people recommended • Phillips Screwdriver	WATTAGE OF FIXTURE.
These instructions are provided for safety. It is very important that	
they are read carefully and completely before beginning installation	
of this chandelier.	CARE INSTRUCTIONS:
We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.	Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.
For customer service questions call 1-800-338-2150	ARTERIORS