ITEM NO.: 45115 NAME: Johanna Pendant	
MATERIAL TYPE: Raffiua FINISH: Natural	
SOCKET TYPE: E26 SOCKET QTY: 1, 3" Neck	
BULB WATTAGE: 150W/CFL 35W/LED 28W	
VOLTAGE: 110-120 V ITEM NET WEIGHT: 40LBS	A se to all
	TO ASSEMBLE:
	1. Shut off the main electrical supply from the main fuse box/circuit breaker.
	<ol> <li>Carefully unpack all fixture parts and hardware and lay them on a so surface for assembly.</li> </ol>
$\begin{array}{c} \textcircled{P} \\ \hline \\ $	<ol> <li>As shown in fig,unscrew the locking ring(e) off the socket assembly(g),and attach the shade(f,not included)from the bottom to the socket</li> </ol>
	properly, then secure it by screw the locking ring(e)till tight.
	4. Gently pull wiring down from ceiling junction box and allow to han
	<ol> <li>Remove mounting plate from the canopy by unscrewing the collar.</li> <li>Carefully inspect the pendant's fixture wires.</li> </ol>
PARTS INCLUDED:	Neutral fixture wire: White Hot fixture wire: Black
A MOUNTING PLATE Qty: 1	Ground wire: Green
B CANOPY Qty: 1	7. Wrap ground wire of lamp assembly and ground wire of junction b
C COLLAR LOOP Qty: 1	together and fasten together with a wire nut and wrap the connect
D RODS Qty: 4	with electrical tape. 8. Attach the neutral fixture wire from the pendant to the neutral
E LOCKING RING Qty: 1	junctionbox wire (usually white). Fasten each together with a wire r
F SHADE Qty: 1	and wrap the connection with electrical tape.
G SOCKET ASSEMBLY Qty: 1	<ol> <li>Attach the hot fixture wire from the pendant to the hot junction bo wire (usually black). Fasten each together with a wire nut and wrap</li> </ol>
HARDWARE INCLUDED:	connection with electrical tape.
H Plastic Wire Connector 2 Pcs Canopy Screws 2 Pcs	DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY
Mounting Screws 2 Pc	WILL BE COMPROMISED.
Green Ground Screw 1 Pc Allen Wrench 1 Pc	10. Gently tuck the wire connections neatly into the ceiling junction b
<b>TO INSTALL YOU WILL NEED:</b> • 2 people recommended       • Phillips Screwdriver	11. Place the mounting plate over the center of the ceiling junction b
These instructions are provided for safety. It is very important	
that they are read carefully and completely before beginning	CARE INSTRUCTIONS:
We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.	Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.
For customer service questions call 1-800-338-2150	ARTERIORS