Ceiling LED Chandelier



START FROM HERE

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- · Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- For dimming, an ELV (Electronic Low Voltage) or TRIAC type of dimmer is required
- 120V input

- 1. Remove fixture from its original package
- 2. Separate mounting plate (1c) from canopy (2a) by removing canopy screws (2b)
- **3.** Attach mounting plate **(1c)** to electrical junction box **(1a)** using junction box screws provided **(1e)** in hardware package
- **4.** Connect quick connectors **(6a)** together and attach rods **(2d)** by threading clockwise
- **5.** To change fixture height, shorten or lengthen wire by removing screw (2c) from canopy (2a) and push or pull wire to your desired length. Secure screw (2c) in canopy (2a) to lock wire in place. Next, push and hold wire gripper (2g), slide wire to desired length and then release wire gripper (2g) to secure
- **6.** Pull wire through aircraft barrel (**5b**) and stopper (**5d**). Secure barrel mount (**5f**), followed by aircraft barrel (**5b**) to mounting surface with anchor (**5c**) and screw (**5a**). Adjust wire to desired length and secure with set screw (**5e**). Insert wire gripper (**2g**) into aircraft barrel (**5b**) to close
- Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package and place driver (4a) inside canopy (2a)
- **8.** Attach canopy **(2a)** to mounting plate **(1c)** with canopy screws **(2b)**



