



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant PrimeMirror™ glass
- Forward-facing task lighting
- Forward-phase dimming technology
- Suitable for damp bathroom environments
- Energy efficient
- Easy installation
- Title 24 compliant
- 3-year limited warranty
- Covered by one or more patents
- Designed in America and sourced globally

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 540 initial lumens per foot
- Maximum raw 96 lumens per watt efficacy
- Calculated L₇₀ 50,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror

PRODUCT DESCRIPTION

Create a sense of Unity™ between light and mirror with the concentric design of a precision inset pattern of light surrounded by a bold reflective border.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror using corrosion-resistant, safety-backed mirror glass. Mirror will offer forward-facing task lighting with uniform light output in frosted areas, using natural-looking LEDs that offer greater than or equal to 90 CRI (color rendering index). Product will be designed in America, sourced globally, and will have a 3-year limited warranty.

THE CORDOVA MIRRORS ADVANTAGE

- ☑ High-quality products at a value price
- ☑ Carefully chosen, globally sourced materials
- ☑ Natural-looking LED lighting for a superior reflection
- ☑ Best-in-class customer service team
- ☑ In-stock products ready for immediate shipments

INSTALLATION SPECIFICATIONS

- 120V hardwire electrical connection; provide 36" whip; junction box not required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by forward-phase dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Initial Lumens Per Fixture	Power Requirements
UNY-2436	24"W x 36"H x 1.81"D (610mm x 914mm x 46mm)	4,320	120 VAC, 47W
UNY-3042	30"W x 42"H x 1.81"D (762mm x 1067mm x 46mm)	5,400	120 VAC, 58W
UNY-3636	36"W x 36"H x 1.81"D (914mm x 914mm x 46mm)	5,400	120 VAC, 58W
UNY-3642	36"W x 42"H x 1.81"D (914mm x 1067mm x 46mm)	5,940	120 VAC, 64W
UNY-4836	48"W x 36"H x 1.81"D (1220mm x 914mm x 46mm)	6,480	120 VAC, 70W

DIMENSIONAL DRAWING (Not to scale.)

