



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Forward-phase dimming technology
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- 7-year limited warranty
- Patent: www.electricmirror.com/patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Ava™ Technology (upgrade)¹
- Defogger
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K (standard)
- CCT: 2,700K, 4,600K, 6,500K color rotation (with Ava)
- Replaceable LEDs
- 73 initial lumens/inch (standard)
- 44 initial lumens/inch (with Ava)
- Maximum 100 lumens/watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ See technology specification sheets for more details

PRODUCT DESCRIPTION

Storied past meets exhilarating present in the prestigious Saratoga™. With sleek lines reflecting strength, grace and elegance, this top-performing lighted mirror is the fixture to bet on for a winning design.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using dimmable, replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S and global components and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Ava controlled by capacitive touch button on fixture or non-dimming on/off wall switch
- Non-Ava model controlled by forward-phase dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

| Base Model* | Base Model* with Ava | Dimensions | Initial Lumens/Fixture | Power Requirements |
|-------------|----------------------|--|----------------------------------|--------------------|
| SAR-2436 | SAR-2436-AE | 24"W x 36"H x 1.75"D (610mm x 914mm x 44mm) | 4,279 standard 3,467 with Ava | 120/240 VAC, 48W |
| SAR-2442 | SAR-2442-AE | 24"W x 42"H x 1.75"D (610mm x 1067mmX 44mm) | 4,938 standard 4,001 with Ava | 120/240 VAC, 57W |

*Base model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

