







PRODUCT DESCRIPTION

A sleek modern design incorporating unpretentious, stylish aesthetic, with a focus on simplicity and minimalism. Blends seamlessly into any any interior or exterior setting. Utilizes a powerful 6-speed operation with an integrated LED luminaire for cost-saving efficiency and luminosity.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Luminaire cover not included
- Includes remote control with wall cradle (RC20-WT)
- Wall control for 3, 4-way control sold separately
- Compatible with WAC Smart Fans app

AIRFLOW/ENERGY EFFICIENCY

4718/6919
23/30
6
77/208
122

SPECIFICATIONS

Construction:	Aluminum, ABS
Blade:	20º Pitch, 60" sweep
Downrod:	3/4"W X 4.5"H included
Mounting Slope:	Up to 30°
Wire:	80″
Hanging Weight:	17 lbs
Total Power:	59W
Standards:	UL/cUL Wet Location listed, Title 24 JA8-2016,
	Title 20, Energy Star
Motor Type:	DC 153 x 20

WIRELESS PERFORMANCE

Wi-Fi Range:	Up to 150 ft*
Bluetooth Range:	Up to 150 ft*

LUMINAIRE PERFORMANCE

Light Source:	LED
Light Wattage:	19.5W
Lumens/Delivered:	1600/517
Dimming:	Integrated
CRI:	90
Color Temperature: Rated	3000K
Life:	50,000 hours

ORDER NUMBER

Model	Housing Blade				
	МВ	Matte Black	МВ	Matte Black	
F-071L	BN	Brushed Nickel	МВ	Matte Black	
	SB	Soft Brass	МВ	Matte Black	

F-071L-

Example: F-071L-MB

*This fan comes uni-pack - blade select options are not available * Range results may vary based on application and surroundings.

The WAC app synchronizes seamlessly with smart home devices you already own



Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Works with

SmartThings

1600 Distribution Ct Lithia Springs, GA 30122

式 ecobee 🚯 Bluetooth Control 🏈 🖉 Јозн

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2021



OPTIONAL ACCESSORIES

Bluetooth Wall Control	WC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	RC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod	DR12-12INDR18-18INDR24-24INDR36-36INDR48-48INDR60-60INDR72-72IN		All our downrods are .75" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers	DC-	MB Matte BlackMW Matte WhiteSB Soft Brass	Connects two downrods together.
Sloped Ceiling Kit	SC-		Designed to accommodate buildings with steeper sloped ceilings up to 45o or 12/12 pitch.

Examples: Wall Control - WC20-WT, Remote Control - RC20-WT, Downrod - DR12-BN, Downrod Coupler - DC-MB, Sloped Ceiling Kit - SC-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-130	14-17o	18-210	22-250	26-290	30-320	33-350	36-380	39-410	42-440	450
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire