

WAC LIGHTING

Volta 2"

Wood And Metal Ceiling Adapter

Model

R2R-ADP1 Round 1/2" to 1"
R2R-ADP2 Round 1" to 1 1/2"
R2S-ADP1 Square 1/2" to 1"
R2S-ADP2 Square 1" to 1 1/2"

Example: **R2R-ADP1**

DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- Adapter installs in field to Volta 2" New Construction housings
- Enables trim to install flush to wood and metal ceilings
- Note: Wall Wash trims to use ADP1 adapter as maximum ceiling thickness is 1"
- 5 year warranty

SPECIFICATIONS

| | |
|--------------------|--------------------------------|
| Construction: | Die-cast Aluminum |
| Cut Out: | 3 15/16" |
| Ceiling Thickness: | 1/2" - 1", 1" - 1 1/2" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C), |
| Standards: | ETL, cETL |

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



WAC LIGHTING

Volta 2"

New Construction Housing Trim Round

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

| Model | Power | Driver | Emergency Backup Battery |
|-----------------------------------|------------------|--|--------------------------------|
| R2RCT Plnm Chic. R2RNT Default | 15 15W 22 22W | Default ELV, 0-10V L1 Lutron Hi-Lume 1% | Default EM-Emergency Backup |

Example: **R2RCT-15**

•For emergency battery backup option, add -EM after the finish R2RCT-22L1EM

DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- EM fixtures provided with integral emergency battery back up with 24" lead wire remote test switch
- Provides at least 90 minutes of 8W illumination during emergency operation.
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

| | |
|--------------------|---|
| Construction: | 20 Gauge cold rolled steel |
| Power: | 15W, 22W |
| Input: | 120-277 VAC, 50/60Hz |
| Dimming: | ELV: 100-5% , 0-10V: 100-0%, Lutron Hi-Lume Ecosystem: 100-1% |
| Mounting: | New construction housings included with universal mounting brackets and hanger bars |
| Cut Out: | 3 9/16" |
| Ceiling Thickness: | 1/2" - 1 1/2" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Default, IC, Airtight, Chicago Plenum Rated Option Available |



REPLACEMENT PARTS

- D-R2N3-22 - 22W Driver
- D-R2N3-15 - 15W Driver

WAC LIGHTING

Volta 2"

New Construction Housing Trim Square

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

| Model | Power | Driver | Emergency Backup Battery |
|-----------------------------------|------------------|--|--------------------------------|
| R2SCT Plnm Chic. R2SNT Default | 15 15W 22 22W | Default ELV, 0-10V L1 Lutron Hi-Lume 1% | Default EM-Emergency Backup |

Example: **R2SCT-15**

•For emergency battery backup option, add -EM after the finish R2SCT-22L1EM

DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- EM fixtures provided with integral emergency battery back up with 24" lead wire remote test switch
- Provides at least 90 minutes of 8W illumination during emergency operation.
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

| | |
|--------------------|---|
| Construction: | 20 Gauge cold rolled steel |
| Power: | 15W, 22W |
| Input: | 120-277 VAC, 50/60Hz |
| Dimming: | ELV: 100-5% , 0-10V: 100-0%, Lutron Hi-Lume Ecosystem: 100-1% |
| Mounting: | New construction housings included with universal mounting brackets and hanger bars |
| Cut Out: | 3 9/16" |
| Ceiling Thickness: | 1/2" - 1 1/2" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Default, IC, Chicago Plenum Rated Option Available |

