

INVISILED® PRO 2

24V LED Tape Light



Tape Section

5 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Ideal for task or accent lighting, InvisILED Pro 2 is a high-performing and modern light system that provides flexible, eco-friendly, and dimmable illumination. Offering three different mounting options, including the 3M construction adhesive on the back for peeling and sticking, enables it to be used in cabinets, counter tops, and coves. 80,000 hours of rated life ensures longevity and a high lumens output.

FEATURES

- Can be field cut, male to male adapter required to re-use female side
- Ultra thin profile at 1/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 6" at the end of a run
- Three (3) mounting method provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 80,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS


- Construction:** Flexible silicone cased tape light, peel and stick 3M construction adhesive on back, indicating marks for field cutting.
- Light Source:** 12 LEDs per foot output, Runs on 24V at 4W per foot
- Operating Temp:** -4°F – 122°F (-20°C – 50°C) at relative humidity 95%
- Standards:** UL & cUL Listed for Damp Locations

ORDER NUMBER – 5 LED "L" CONNECTOR

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Title 24	Tape Color
LED-TX24 2	22	2200K	90	110	No	5L-WT White
	27	2700K	90	130	Yes	
	30	3000K	90	130	Yes	
	35	3500K	90	135	Yes	
	45	4500K	85	135	No	

LED-TX24 ___ -5L-WT

Example: LED-TX2435-5L-WT



ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Title 24	Length	Qty	Tape Color
LED-TX24 4	22	2200K	90	275	No	6IN	6 inches	1
	27	2700K	90	325	Yes	1	1 foot	1
	30	3000K	90	300	Yes	1-40	1 foot	40
	35	3500K	90	330	Yes	5	5 feet	1
	45	4500K	85	330	No			

LED-TX24 ___ - ___ -WT

Example: LED-TX2445-1-40-WT

Class 2 Power Supply (Required)

	Model	Input	Output	Max Run	Dimming	Description
	EN-2460-RB2-T EN-24100-RB2-T	Remote	120VAC 120VAC	24VAC / 60W 24VAC / 96W	15' 25'	100%-5% ELV UL Class 2 output.
	PS-24DC-U60R-T PS-24DC-U96R-T	Remote	120-277VAC	24VDC / 60W 24VDC / 96W	15' 25'	100%-5% ELV, TRIAC UL Class 2 output.
	EN-24100-277-RB2-T	Remote	277VAC	24VDC / 96W	25'	100%-5% 0-10V UL Class 2 output.
	EN-2460-P-AR-T EN-24100-P-AR-T	Plug-in	120VAC 120VAC	24VAC / 60W 24VAC / 96W	15' 25'	Non Dimmable UL Class 2 output.
	EN-D24100-120-R	Wall Dimmer & Driver	120VAC	24VDC / 96W	25'	Integral UL Class 2 output.

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122



Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91761

INVISILED® PRO 2

24V LED Tape Light



Indoor Controller

	Model		Description
	CT-6A-R2	Pro, Pro2, Pro3, LITE	Touch Panel and Motion Sensor Includes a Touch Panel, Occupancy Sensor and a Controller. AC/DC input at 12V(60W Max) or 24V(96W Max). Connect on secondary side of driver/transformer.
	IR-96-24VACDC-WT IR-96-24VACDC-BK	White Black	IR Sensor IR (Infrared sensor) switch works by turning the light on when it becomes unobstructed.





Indoor Electrical Accessories

	Model	Dimension	Finish	Description
	LED-TC-WEXT-144 LED-TC-WEXT-144-WT LED-TC-WEXT-240 LED-TC-WEXT-240-WT	12 ft 12 ft 20 ft 20 ft	Black White Black White	In Wall Rated Extension Cable Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-WIC-144 LED-TC-WIC-144-WT LED-TC-WIC-240 LED-TC-WIC-240-WT	12 ft 12 ft 20 ft 20 ft	Black White Black White	In Wall Rated Joiner Cable Connects tape sections. 2 female ends. 1 male to male connector included.
	LED-TC-P-2 LED-TC-P-2-WT LED-TC-P-12 LED-TC-P-12-WT	2 ft 2 ft 12 ft 12 ft	Black White Black White	Lead Wire Alternative lengths for plug-in power supplies.
	LED-TC-EXT-144 LED-TC-EXT-144-WT	12 ft 12 ft	Black White	Extension Cable Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-B-2 LED-TC-B-2-WT	L: 1½ in W: ¾ in H: 7⁄8 in	Black White	Low Voltage Wiring Box With Feed Neatly houses connections for up to two wires with 12" female feed.
	LED-T-B	L: 1½ in W: ¾ in H: 7⁄8 in	White	Low Voltage Wiring Box Neatly houses connections for up to two wires.
	TB-S	L: 6¼ in W: 1½ in H: 1¼ in	White	Wiring Box With Switch Use when spanning a large gap in a system layout without leaving exposed wiring. Optional switch included.

Compatible with Pro, Pro2, Pro3, LITE.

	Model	Dimension	Finish	Description
	LED-TC-IC2 LED-TC-IC2-WT LED-TC-IC6 LED-TC-IC6-WT LED-TC-IC12 LED-TC-IC12-WT LED-TC-IC36 LED-TC-IC36-WT LED-TC-IC72 LED-TC-IC72-WT	2 in 2 in 6 in 6 in 12 in 12 in 36 in 36 in 72 in 72 in	Black White Black White Black White Black White Black White	Joiner Cable Connects tape sections.
	LED-TC-MM	50 Qty	Black	Connector Male to male connector.

Compatible with Pro, Pro2, Pro3, LITE. Change directionality of tape runs and reuse cut ends of tape.

	Model	Finish	Description
	LED-TC-Y LED-TC-Y-WT	Black White	3-Way "Y" Connector Connects tape sections.
	LED-TC-X LED-TC-X-WT	Black White	4-Way "X" Connector Connects tape sections.
	LED-TC-L LED-TC-L-WT	Black White	"L" Connector Connects tape sections.
	LED-TC-EC LED-TC-EC-WT	Black White	End Cap 1 cut and 1 male end cap.

Compatible with Pro, Pro2, Pro3, LITE.

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91761

INVISILED® PRO 2

Indoor Aluminum Channels

WAC



Aluminum Channel **LED-T-CH** 5 feet
Additional End Caps **LED-T-CH-EC** 2 pcs

*Diffuses light from InvisiLED® tape
 Includes a diffuser, two end caps, and five screws*



Deep Aluminum Channel **LED-T-CH1** 5 feet
Additional End Caps **LED-T-CH1-EC** 2 pcs

*Eliminates visible hot spots
 Includes a diffuser, two end caps, and five screws*



45° Angled Aluminum Channel **LED-T-CH2** 5 feet
Additional End Caps **LED-T-CH2-EC** 2 pcs

Includes a diffuser, two end caps, and five screws



Deep Aluminum Channel - Flood 54° Beam Angle **LED-T-CH3-FL** 5 feet
Additional End Caps **LED-T-CH1-EC** 2 pcs

Eliminates visible hot spots / 54° beam angles



Deep Aluminum Channel - Spot 9° Beam Angle **LED-T-CH3-SP** 5 feet
Additional End Caps **LED-T-CH1-EC** 2 pcs

Eliminates visible hot spots / 9° beam angles




Deep Aluminum Channel - Wide Flood 84° Beam Angle **LED-T-CH3-WF** 5 feet
Additional End Caps **LED-T-CH1-EC** 2 pcs

Eliminates visible hot spots / 84° beam angles



Fixed Angle Channel Clip **LED-T-CL3-PT**

Includes 2 pieces, 4 screws. Use to mount Aluminum Channel.



Adjustable Channel Clip **LED-T-CL2-PT**

*Includes 2 pieces, 4 screws. Used to mount Aluminum Channel.
 Adjusts 50° from center either way.*

INDOOR MOUNTING ACCESSORIES



Aluminum Retrofit Channel **LED-T-RC** 3 feet

Can be bent to create fixed curves or used as a glare shield



Clip **LED-T-CL** **Curve Clip** **LED-T-CL1**

*For surfaces that are difficult to adhere.
 Includes: 10 pcs plastic clips and 10 pcs screws.
 Compatible with InvisiLED LITE, PRO,
 PRO2 and PRO3 only.*

*Clips to hold indoor InvisiLED tapes
 sections. Includes: 10 pcs plastic clips and
 10 pcs screws. Compatible with InvisiLED
 LITE, PRO, PRO2 and PRO3 only.*

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050


Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91761

INVISILED® PRO 2

Symmetrical Recessed Channel

WAC




- Installs within $\frac{5}{8}$ " drywall depth
- Linear channel can be field cut
- Accommodates either one or two runs of indoor tape
- Includes a translucent white acrylic diffuser
- Dense foam insert to be removed in installation after spackling

8ft Linear Channel

LED-T-RCH1-WT

- Includes: 1 diffuser
- 8 perforated metal sheets





Power Feed

LED-T-RBOX1-WT

- The end cap may be placed on either side
- Hanger bars may be installed on any side of the wiring box
- Kit includes:


- 1 wiring box
- 2 hanger bars
- 4 five-pin adapters
- 2 end caps
- 1 diffuser
- 2 channel connectors
- 1 counter sink drill bit
- 1 drill bit
- 1 installation tool



Lateral Corner

LED-T-CTC1-WT


- Includes: Diffuser
- 2 channel connectors
- 2 perforated metal sheets



Perpendicular Corner

LED-T-WTC1-WT


- Transitions between walls or wall to ceiling
- Includes: Diffuser
- 2 channel connectors
- 2 perforated metal sheets



Outside Corner

LED-T-WTW1-WT

- Transitions around columns, bump outs, or soffits
- Includes: Diffuser
- 2 channel connectors
- 2 perforated metal sheets



waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050


Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91761

INVISILED® PRO 2

Asymmetrical Recessed Channel


WAC



Installs within 5/8" drywall depth
 Linear channel can be field cut
 Accommodates one run of indoor tape
 Dense foam insert to be removed in installation after spackling
 Recommended installation within 15 inches of surface to be illuminated

8ft Linear Channel **LED-T-RCH2-WT**



Includes: 8 perforated metal sheets
 2 channel connectors




Power feed **LED-T-RBOX2-WT**

The end cap may be placed on either side
 Hanger bars may be installed on any side of the wiring box


Includes: 1 wiring box
 2 hanger bars
 2 five-pin adapters
 2 end caps (left and right)
 2 channel connectors
 1 counter sink bit
 1 drill bit



Indirect Recessed Channel




Linear channel can be field cut
 Accommodates up to four runs of indoor tape
 Dense foam insert to be removed in installation after spackling
 Allows option to use different color tape in one channel and switch them separately



8ft Linear Channel **LED-T-RCH3-WT**





Includes: 10 perforated metal sheets
 2 channel connectors



Power feed **LED-T-RBOX3-WT**

The end cap may be placed on either side
 Hanger bars may be installed on any side of the wiring box

Includes: 1 wiring box
 2 hanger bars
 4 five-pin adapters
 1 end cap
 2 channel connectors
 1 counter sink drill bit
 1 drill bit



wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91761