

# INVISILED® PRO 3

## 24V High Output Foldable LED Tape Light

# WAC



Tape Section

Foldable Capability

Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

A specification grade tape light that is designed for task or accent lighting applications. This tape can be folded to create customized patterns with the help of LED-T-CL1 clips for a flattering look. Pro3 is equipped with evenly spaced diodes at 1" on the center to prevent dark spots and can be field-cut at 6" at the end of a run to perfectly fit into your interior space.

### FEATURES

- Can be field cut, male to male adapter required to re-use female side
- Foldable design for lateral pattern creation
- Install LED-T-CL1 clips with folds
- Ultra thin profile at 1/8". 90° fold height of 3/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 6" at the end of a run
- Three mounting methods provided for different surfaces
- 70,000 hour rated life
- 5 year WAC Lighting product warranty

### SPECIFICATIONS


- Construction:** Flexible silicone cased tape light, peel and stick 3M construction adhesive on back, indicating marks for field cutting.
- Light Source:** 12 LEDs per foot, Runs on 24V at 5W per foot
- Operating Temp:** -4°F – 104°F (-20°C – 40°C), relative humidity 95%
- Standards:** UL & cUL Listed for Damp Locations

### ORDER NUMBER – TAPE SECTION

Model	Watts/ft	ColorTemp	CRI	Lumens/ft	Length	Qty	Tape Color
<b>LED-TE24</b> 5	<b>27</b>	2700K	95	385	<b>6IN</b>	6 inches	1
	<b>30</b>	3000K	95	395	<b>1</b>	1 foot	1
	<b>35</b>	3500K	90	440	<b>5</b>	5 feet	1
	<b>45</b>	4500K	90	475	<b>1-40</b>	1 foot	40
							<b>WT</b> White

**LED-TE24** \_\_\_ - \_\_\_ - **WT**

Example: **LED-TE2445-6IN-WT**



### Class 2 Power Supply (Required)

	Model	Input	Output	Max Run	Dimming	Description
	EN-2460-RB2-T	120VAC	24VAC / 60W	12'	100%-5% ELV	Includes a 6' lead wire. UL Class 2 output.
	EN-24100-RB2-T	120VAC	24VAC / 96W	20'		
	PS-24DC-U60R-T	120-277VAC	24VDC / 60W	12'	100%-5% ELV, TRIAC	Includes a 6' lead wire. UL Class 2 output.
	PS-24DC-U96R-T	120-277VAC	24VDC / 96W	20'		
	EN-24100-277-RB2-T	277VAC	24VDC / 96W	20'	100%-5% 0-10V	Includes a 6' lead wire. UL Class 2 output.
	EN-2460-P-AR-T	120VAC	24VAC / 60W	12'	Non Dimmable	Includes a 6' lead wire. UL Class 2 output.
	EN-24100-P-AR-T	120VAC	24VAC / 96W	20'		
	EN-D24100-120-R	120VAC	24VDC / 96W	20'	Integral	Includes a 6' lead wire. UL Class 2 output.

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122



Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91761

# INVISILED® PRO 3

## 24V High Output Foldable LED Tape Light



### Indoor Controller

	Model		Description
	CT-6A-R2	Pro, Pro2, Pro3, LITE	<b>Touch Panel and Motion Sensor</b> Includes a Touch Panel, Occupancy Sensor and a Controller. AC/DC input at 12V(60W Max) or 24V(96W Max). Connect on secondary side of driver/transformer.
	IR-96-24VACDC-WT IR-96-24VACDC-BK	White Black	<b>IR Sensor</b> IR (Infrared sensor) switch works by turning the light on when it becomes unobstructed.





### Indoor Electrical Accessories

	Model	Dimension	Finish	Description
	LED-TC-WEXT-144 LED-TC-WEXT-144-WT LED-TC-WEXT-240 LED-TC-WEXT-240-WT	12 ft 12 ft 20 ft 20 ft	Black White Black White	<b>In Wall Rated Extension Cable</b> Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-WIC-144 LED-TC-WIC-144-WT LED-TC-WIC-240 LED-TC-WIC-240-WT	12 ft 12 ft 20 ft 20 ft	Black White Black White	<b>In Wall Rated Joiner Cable</b> Connects tape sections. 2 female ends. 1 male to male connector included.
	LED-TC-P-2 LED-TC-P-2-WT LED-TC-P-12 LED-TC-P-12-WT	2 ft 2 ft 12 ft 12 ft	Black White Black White	<b>Lead Wire</b> Alternative lengths for plug-in power supplies.
	LED-TC-EXT-144 LED-TC-EXT-144-WT	12 ft 12 ft	Black White	<b>Extension Cable</b> Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-B-2 LED-TC-B-2-WT	L: 1½ in W: ¾ in H: 7⁄8 in	Black White	<b>Low Voltage Wiring Box With Feed</b> Neatly houses connections for up to two wires with 12" female feed.
	LED-T-B	L: 1½ in W: ¾ in H: 7⁄8 in	White	<b>Low Voltage Wiring Box</b> Neatly houses connections for up to two wires.
	TB-S	L: 6¼ in W: 1½ in H: 1¼ in	White	<b>Wiring Box With Switch</b> Use when spanning a large gap in a system layout without leaving exposed wiring. Optional switch included.

Compatible with Pro, Pro2, Pro3

	Model	Dimension	Finish	Description
	LED-TC-IC2 LED-TC-IC2-WT LED-TC-IC6 LED-TC-IC6-WT LED-TC-IC12 LED-TC-IC12-WT LED-TC-IC36 LED-TC-IC36-WT LED-TC-IC72 LED-TC-IC72-WT	2 in 2 in 6 in 6 in 12 in 12 in 36 in 36 in 72 in 72 in	Black White Black White Black White Black White Black White	<b>Joiner Cable</b> Connects tape sections.
	LED-TC-MM	50 Qty	Black	<b>Connector</b> Male to male connector.

Compatible with Pro, Pro2, Pro3, LITE. Change directionality of tape runs and reuse cut ends of tape.

	Model	Finish	Description
	LED-TC-Y LED-TC-Y-WT	Black White	<b>3-Way "Y" Connector</b> Connects tape sections.
	LED-TC-X LED-TC-X-WT	Black White	<b>4-Way "X" Connector</b> Connects tape sections.
	LED-TC-L LED-TC-L-WT	Black White	<b>"L" Connector</b> Connects tape sections.
	LED-TC-EC LED-TC-EC-WT	Black White	<b>End Cap</b> 1 cut and 1 male end cap.

Compatible with Pro, Pro2, Pro3, LITE.

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91761

# INVISILED® PRO 3

## Indoor Aluminum Channels

# WAC



**Aluminum Channel**      **LED-T-CH**      5 feet  
**Additional End Caps**      **LED-T-CH-EC**      2 pcs

*Diffuses light from InvisiLED® tape  
 Includes a diffuser, two end caps, and five screws*



**Deep Aluminum Channel**      **LED-T-CH1**      5 feet  
**Additional End Caps**      **LED-T-CH1-EC**      2 pcs

*Eliminates visible hot spots  
 Includes a diffuser, two end caps, and five screws*



**45° Angled Aluminum Channel**      **LED-T-CH2**      5 feet  
**Additional End Caps**      **LED-T-CH2-EC**      2 pcs

*Includes a diffuser, two end caps, and five screws*



**Deep Aluminum Channel - Flood 54° Beam Angle**      **LED-T-CH3-FL**      5 feet  
**Additional End Caps**      **LED-T-CH1-EC**      2 pcs

*Eliminates visible hot spots / 54° beam angles*



**Deep Aluminum Channel - Spot 9° Beam Angle**      **LED-T-CH3-SP**      5 feet  
**Additional End Caps**      **LED-T-CH1-EC**      2 pcs

*Eliminates visible hot spots / 9° beam angles*




**Deep Aluminum Channel - Wide Flood 84° Beam Angle**      **LED-T-CH3-WF**      5 feet  
**Additional End Caps**      **LED-T-CH1-EC**      2 pcs

*Eliminates visible hot spots / 84° beam angles*



**Fixed Angle Channel Clip**      **LED-T-CL3-PT**

*Includes 2 pieces, 4 screws. Use to mount Aluminum Channel.*



**Adjustable Channel Clip**      **LED-T-CL2-PT**

*Includes 2 pieces, 4 screws. Used to mount Aluminum Channel.  
 Adjusts 50° from center either way.*

## INDOOR MOUNTING ACCESSORIES



**Aluminum Retrofit Channel**      **LED-T-RC**      3 feet

*Can be bent to create fixed curves or used as a glare shield*



**Clip**      **LED-T-CL**      **Curve Clip**      **LED-T-CL1**

*For surfaces that are difficult to adhere.  
 Includes: 10 pcs plastic clips and 10 pcs screws.  
 Compatible with InvisiLED LITE, PRO,  
 PRO2 and PRO3 only.*

*Clips to hold indoor InvisiLED tapes  
 sections. Includes: 10 pcs plastic clips and  
 10 pcs screws. Compatible with InvisiLED  
 LITE, PRO, PRO2 and PRO3 only.*

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050


Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91761

# INVISILED® PRO 3

## Symmetrical Recessed Channel

# WAC




- Installs within  $\frac{5}{8}$ " drywall depth
- Linear channel can be field cut
- Accommodates either one or two runs of indoor tape
- Includes a translucent white acrylic diffuser
- Dense foam insert to be removed in installation after spackling

### 8ft Linear Channel

### LED-T-RCH1-WT

- Includes: 1 diffuser
- 8 perforated metal sheets





### Power Feed

### LED-T-RBOX1-WT

- The end cap may be placed on either side
- Hanger bars may be installed on any side of the wiring box
- Kit includes:

- 1 wiring box
- 2 hanger bars
- 4 five-pin adapters
- 2 end caps
- 1 diffuser


- 2 channel connectors
- 1 counter sink drill bit
- 1 drill bit
- 1 installation tool



### Lateral Corner

### LED-T-CTC1-WT


- Includes: Diffuser
- 2 channel connectors
- 2 perforated metal sheets



### Perpendicular Corner

### LED-T-WTC1-WT


- Transitions between walls or wall to ceiling
- Includes: Diffuser
- 2 channel connectors
- 2 perforated metal sheets



### Outside Corner

### LED-T-WTW1-WT

- Transitions around columns, bump outs, or soffits
- Includes: Diffuser
- 2 channel connectors
- 2 perforated metal sheets



waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050


Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91761

# INVISILED® PRO 3

## Asymmetrical Recessed Channel


# WAC



Installs within 5/8" drywall depth  
 Linear channel can be field cut  
 Accommodates one run of indoor tape  
 Dense foam insert to be removed in installation after spackling  
 Recommended installation within 15 inches of surface to be illuminated

### 8ft Linear Channel **LED-T-RCH2-WT**



Includes: 8 perforated metal sheets  
 2 channel connectors




### Power feed **LED-T-RBOX2-WT**

The end cap may be placed on either side  
 Hanger bars may be installed on any side of the wiring box


Includes: 1 wiring box  
 2 hanger bars  
 2 five-pin adapters  
 2 end caps (left and right)  
 2 channel connectors  
 1 counter sink bit  
 1 drill bit



## Indirect Recessed Channel




Linear channel can be field cut  
 Accommodates up to four runs of indoor tape  
 Dense foam insert to be removed in installation after spackling  
 Allows option to use different color tape in one channel and switch them separately



### 8ft Linear Channel **LED-T-RCH3-WT**





Includes: 10 perforated metal sheets  
 2 channel connectors



### Power feed **LED-T-RBOX3-WT**

The end cap may be placed on either side  
 Hanger bars may be installed on any side of the wiring box

Includes: 1 wiring box  
 2 hanger bars  
 4 five-pin adapters  
 1 end cap  
 2 channel connectors  
 1 counter sink drill bit  
 1 drill bit



wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91761