Quill

Mini Pendant 4CCT

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-59416 16"	2700K 3000K 3500K 4000K	AB Aged Brass BK Black CH Chrome	8 W 8 W 8 W 8 W	670 670 670 670	577 577 577 577

Example: **PD-59416-40-CH**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Precisely lined. V-groove flared glass radiates a prismatic glow. Staggered elements create a sense of motion, heightening the drama of this statement

FEATURES

- V cut glass diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

3500K,3000K,4000K,2700K Color Temp:

120/277V,50/60Hz Input:

90 CRI:

Dimming: ELV: 100-10% ,TRIAC: 100-5%

50000 Hours Rated Life: ETL, cETL Standards:

Damp Location Listed


Construction: Aluminum Hardware with Glass body



FINISHES:



LINE DRAWING:



PD-59416