Fixture	Type:
---------	-------

Project:

Location:

Viggo

Round Multi Light 4CCT

Model & Size	Color Temp & CRI		Watt	Lumens	Finish
PD-69403R1 24" - 3 Lights	2 700K/3000K/3500K/4000K	90	15 W	401	BK Black

Example: PD-69403R1-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120/277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL
	Damp Location Listed
Construction:	Aluminum body with etched acrylic diffuser



FINISHES:



RPL-GLA-69424 - Acrylic Diffuser



LINE DRAWING:

Project:

Location:

Viggo

Round Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
PD-69403R2 32" - 3 Lights	2 700K/3000K/3500K/4000K 9	15 W	401	BK Black

Example: PD-69403R2-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

REPLACEMENT PARTS

RPL-GLA-69424 - Acrylic Diffuser


Color Temp:	2700K/3000K/3500K/4000K
Input:	120/277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL
	Damp Location Listed
Construction:	Aluminum body with etched acrylic diffuser



FINISHES:



LINE DRAWING:



PD-69403R2

Project:

Location:

Viggo

Round Multi Light 4CCT

Model & Size	Color Temp & CRI		Watt	Lumens	Finish
PD-69405R1 24" - 5 Lights	2 700K/3000K/3500K/4000K	90	20 W	536	BK Black

Example: PD-69405R1-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES


- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120/277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL
	Damp Location Listed
Construction:	Aluminum body with etched acrylic diffuser




FINISHES:



RPL-GLA-69424 - Acrylic Diffuser

LINE DRAWING:

Black



PD-69405R1

Project:

Location:

Viggo

Round Multi Light 4CCT

Model & Size	Color Temp & CRI		Watt	Lumens	Finish
PD-69405R2 32" - 5 Lights	2 700K/3000K/3500K/4000K	90	20 W	536	BK Black

Example: PD-69405R2-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120/277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL
	Damp Location Listed
Construction:	Aluminum body with etched acrylic diffuser




FINISHES:



RPL-GLA-69424 - Acrylic Diffuser



LINE DRAWING:



PD-69405R2

Project:

Location:

Viggo

Round Multi Light 4CCT

Model & Size	Color Temp & CRI	W	Vatt	Lumens	Finish
PD-69409R 32" - 9 Lights	2 700K/3000K/3500K/4000K	4 (90	0 W	1071	BK Black

Example: PD-69409R-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES


- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120/277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL
	Damp Location Listed
Construction:	Aluminum body with etched acrylic diffuser




FINISHES:



RPL-GLA-69424 - Acrylic Diffuser



LINE DRAWING:



PD-69409R

Project:

Location:

Viggo

Round Multi Light 4CCT

Model & Size	Color Temp & CRI		Watt	Lumens	Finish
PD-69415R 32" - 15 Lights	2 700K/3000K/3500K/4000K	90	65 W	1741	BK Black

Example: PD-69415R-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120/277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL
	Damp Location Listed
Construction:	Aluminum body with etched acrylic diffuser




FINISHES:



REPLACEMENT PARTS

RPL-GLA-69424 - Acrylic Diffuser

LINE DRAWING:



PD-69415R

Project:

Location:

Viggo

Round Multi Light 4CCT

Model & Size	Color Temp & CRI		Watt	Lumens	Finish
PD-69421R 32" - 21 Lights	2 700K/3000K/3500K/4000K	90	75 W	2008	BK Black

Example: PD-69421R-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

REPLACEMENT PARTS

RPL-GLA-69424 - Acrylic Diffuser

Color Temp:	2700K/3000K/3500K/4000K
Input:	120/277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL
	Damp Location Listed
Construction:	Aluminum body with etched acrylic diffuser




FINISHES:



Black

LINE DRAWING:



PD-69421R