


# Calipso Linear 120 ceiling 3000K white

## SPECIFICATIONS

0220018ADIM



### Design By

Neil Poulton

### Collection

Design



### Specifications

Delivered lumens	2985lm
Light output ratio	69lm/W
Power consumption	43W
Led type	38W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire**
Input Voltage	120-277V
Driver	ERP POWER - 1 x PHB50W-1200-42

### Colors & Finishes

White

\*Integrated light source \*\*2-wire dimming at 120VAC only



### Materials

- Louvers in ASA (Acrylonitrile Styrene Acrylate)

### Features & Accessories

- The fractal shape of the small circles works as an optical grid
- Fractal shape of an impure geometry
- Direct diffused light output

### Dimensions



### Packaging

1 Box


1 x 52-7/8" x 6-3/8" x 11-5/16" / 10.84 lbs - 134 cm x 16 cm x 28.5 cm / 4.915 kg

### Light distribution

Direct

### Luminaire weight

7.63 lbs / 3.46 kg



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

### Warranty

last updated: 2022-10-26

We reserve the right to change specifications of our products.  
For the latest product information please visit [www.artemide.net](http://www.artemide.net)

**Artemide**