

Ross Lovegrove

#### Collection =

Design



#### Colors & Finishes =



## Materials =

- Reflective unit in ABS injection-molded mirror treated
- Lighting unit in die-cast aluminum mirror treated
- Bearing structure in painted steel

### Specifications —


•	
Delivered lumens	1300lm
Light output ratio	45lm/W
Power consumption	29W
Led type	27W C.O.B.*
CCT (Correlated Color Temperature)	2700K
CRI (Color Rendering Index)	>93
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire
Input Voltage	120-277V
Driver	HATCH - 1 x XTC32-0700P-UNV-I

<sup>\*</sup>Integrated light source

#### Features & Accessories =

- Without integrated lighting unit (non-electrified)
- Optional template available to help assemble multiple units
- Possible to obtain a numerous range of configurations simply by adding extra units

#### Dimensions =




# Packaging =

1 x 34-3/4" x 30" x 26-7/8" / 51.59 lbs - 88 cm x 76 cm x 68 cm / 23.4 kg

### Light distribution =

Indirect



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

# Luminaire weight =

29.23 lbs / 13.26 kg

#### Warranty =

5 year limited warranty

