




ASSEMBLY INSTRUCTION MODEL #ZAN-9011-SG



Rod + Chain hung



All electrical components must be

WARNING:

installed by a licensed electrician

in accordance with the National

Electric Code and the appropriate

Local electrical codes.





You will need 1 -Medium Base Bulb

60 Watts recommended 100 Watts Max.

USE LED BULBS FOR EXTENDED USE THIS FIXTURE IS DAMP RATED

How to Install

For rod hung

- 1. Decide the preferred hanging height and choose the correct rod length needed.
- Feed the wire through the rods and connect them together. Screw one end of the rod assembly onto the top of the fixture. Screw the loop onto the other end of the rod assembly and connect it to the collar loop using the quick link.

For rod + chain hung

- 1. Decide the preferred hanging height and choose the correct rod and chain length needed.
- Feed the wire through the rods and connect them together. Screw one end of the rod assembly onto the top of the fixture and screw the loop onto the other end. Using the quick links, attach one end of the chain to the collar loop and the other to the loop on the rod assembly.

For chain hung


- 1. Decide the preferred hanging height and choose the correct chain length needed.
- 2. Screw the loop onto the top of the fixture.
- Feed the wire through the chain links. Using the quick links, attach one end of the chain link to the collar loop and the other end to the loop.

WARNING: This product can expose you to Lead, which is known to the State of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov.





PART NUMBER MODEL #ZAN-9011-SG



Part Number

- A. (1) Mounting Hardware
- B. (1) Canopy(W5.0",H0.8") #XLF9003SGCAN5IN
- C. (1) Collar Ring
- D. (1) Collar Loop
- E. (2) Quick Link(5mm)
- F. (1) Hanging Chain(72",4.5mm) #XLF9003SGCHA4.5MM
- G. (1) Loop #XLF9003SGL00P
- H. (2) Rod(D0.5",L12") #XLF9003SGROD12IN
 I. (1) Rod(D0.5",L6") #XLF9003SGROD6IN

