Thornwood Linear Chandelier

6626308 1.0

Visual Comfort & Co.

STUDIO COLLECTION

CAUTION - RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°c supply conductors.

GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.

Incandescent version may be dimmed with a standard incandescent dimmer. LED version may be dimmed with a LED dimmer. Consult lamp manufacturer for additional information.


This instruction shows a typical installation.

VISUAL COMFORT & CO.

7400 Linder Ave, Skokie, IL 160077 800.969.3347


www.visualcomfort.com

©2023 Visual Comfort & Co.. All rights reserved. The Visual Comfort & Co. logo is a registered trademark of Visual Comfort & Co. Visual Comfort & Co. reserves the right to change specifications for product improvements without notification



SAVETHESE INSTRUCTIONS!

Install the Fixture



- Temporarily install the mounting plate to the junction box.
- 2 Mark the anchor locations through the holes on the mounting plate. Remove the mounting plate.
- 3 Drill appropriate sized holes at the marked locations and install the anchors.
- 4 Secure the mounting plate to the junction box and screw the anchor screw into the anchors.
- Install the candle tubes by sliding them over the sockets.
- 6 Screw the lamps into the sockets. Refer to the label on the socket for Max Wattage information.
- Determine the wanted height or look of the fixture with the provided stems and assemble them by screwing them together. All parts may be used alone or in used in combination.
- B Feed the fixture wires through the stem assembly, then screw the stem assemblies onto the top of the fixture.
- 9 Feed the fixture wires through the pivot and canopy, then screw the pivots onto the stem assemblies.
- Connect the fixture to a suitable ground in accordance to local electrical codes.
- Connect the white fixture wire (square and/or rigid) to the neutral power line wire with a wire nut.
- Connect the black fixture wire (round and/or smooth) to the hot power line wire with a wire nut.
- Neatly place all the wires into the junction box, place the canopy onto the mounting studs, and secure it in place by screwing the cap nuts onto the studs.