


ADELPHI Vanity
3-537-xx

oxygen

FIXTURE TYPE _____ LOCATION _____
PROJECT _____ DATE _____




-24 Satin Nickel



-15 Black



-22 Oiled Bronze



-40 Aged Brass

| | |
|-----------------------------|---|
| LIGHT SOURCE | 1 x 11.7W LED, 3000K, CRI 90 |
| LUMINAIRE POWER | 14.1W at 120V |
| RATED LIFE | 60000 hr RL |
| OPTIONAL COLOR TEMPERATURES | 2700K, 3500K, 4000K |
| LUMEN OUTPUT | Delivered: 1258 lm (LM-79) |
| INPUT VOLTAGE | 120V to 277V AC, 50/60Hz |
| DRIVER OUTPUT | 350mA, 14.7W max power |
| DIMMING | TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output |
| CONSTRUCTION | Plated Steel and Acrylic |
| DIFFUSER | - Matte White Acrylic |
| FINISHES | Black (-15), Oiled Bronze (-22), Satin Nickel (-24), Aged Brass (-40) |
| MOUNTING | 4" Octagonal J-Box, 4" Square J-Box, 4" Square J-Box with single device mud ring, 4" Square J-Box with round mud ring (2.75" center to center mounting) |
| STANDARDS | UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0. |



DIMENSIONS

| | |
|------|---------------------------|
| W: | 24.25" |
| H: | 4.75" |
| Ext: | 3.50" |
| M.C: | 2.37" From top of fixture |

Order example for standard fixture:

3-537-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V to 277V

Order example for optional color temperatures: **3-537-2724**

27: 2700K, 35: 3500K, 40: 4000K

