

# DIONE Ceiling Mount

Universal Voltage: **32-664-24**

# oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_


PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel

LIGHT SOURCE	1 x 9.7W LED, 3000K, CRI 90
LUMINAIRE POWER	11.2W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 422 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	350mA, 15W max power
DIMMING	0-10V dimming, 100% to 10% dimming range
CONSTRUCTION	Plated Steel and Glass
DIFFUSER	- Frosted Glass
FINISHES	Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box
STANDARDS	UL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**  
Dia: 15.00"  
H: 2.25"

Order example for standard fixture:

**32-664-24** (x- Voltage - xxx-Sequence # - xx-Finish)

32: Universal Voltage

Order example for optional color temperatures: **32-664-2724**

27: 2700K, 35: 3500K, 40: 4000K

