

**FAVERO Wall Sconce**  
**3-402-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel



-40 Aged Brass

**LIGHT SOURCE** (2x) 3W LED Arrays, 3000K, CRI 90

**LUMINAIRE POWER** 7.3W Input Power

**RATED LIFE** 60000 hr RL

**OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K

**LUMEN OUTPUT** Delivered: 208 lm (LM-79)

**INPUT VOLTAGE** 120V to 277V AC, 50/60Hz

**DRIVER OUTPUT** 180mA, 7.6W max power

**DIMMING** TRIAC and ELV dimming at 120V AC;  
0-10V dimming, 100% to 10% current output

**CONSTRUCTION** Cold Rolled Steel Housing


**DIFFUSER** - Matte White Acrylic

**FINISHES** Satin Nickel (-24), Aged Brass (-40)

**MOUNTING** Center of fixture (8.25" from top): 2"x3" J-Box,  
4" Square J-Box with a single device mud ring

Top of fixture (2.5" from top): 2"x3" J-Box, 4" Octagonal J-Box,  
4" Square J-Box, 4" Square J-Box with a single device mud ring

**STANDARDS** cUL Damp Listed, ADA Compliant, Conforms to  
UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

**W:** 4.6875"  
**H:** 16.50"  
**Ext:** 3.125"  
**M.C:** 8.25"/2.50" From top of fixture

Order example for standard fixture:

**3-402-40** (x-xxx: LED Sequence # / -xx: Finish)

Order example for optional color temperatures: **3-402-2740**

27: 2700K, 35: 3500K, 40: 4000K

