

LUNA Pendant
3-670-xx


oxygen

FIXTURE TYPE _____ LOCATION _____
PROJECT _____ DATE _____



-22 Oiled Bronze -20 Polished Nickel -24 Satin Nickel -40 Aged Brass

LIGHT SOURCE	1 x 5.1W LED, 3000K, CRI 90
LUMINAIRE POWER	7.2W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 368 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	180mA, 7.6W max power
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
CONSTRUCTION	Plated Steel and Glass
DIFFUSER	- White Opal Glass
FINISHES	Polished Nickel (-20), Oiled Bronze (-22), Satin Nickel (-24), Aged Brass (-40)
MOUNTING	4" Octagonal J-Box*, 4" Square J-Box* with a single device mud ring *Deep J-Box (Required to house driver)
STANDARDS	UL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS
Dia. Canopy: 5.88"
W. Fixture: 6.00"
H. Fixture: 8.25"
Supplied with 10 ft braided cord

Order example for standard fixture:
3-670-24 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V to 277V
Order example for optional color temperatures: **3-670-2724**
27: 2700K, 35: 3500K, 40: 4000K

