

LUNA Pendant

3-670-xx

oxygen

FIXTURE TYPE _____ LOCATION _____
 PROJECT _____ DATE _____



-22 Oiled Bronze -20 Polished Nickel -24 Satin Nickel -40 Aged Brass

LIGHT SOURCE 1 x 5.1W LED, 3000K, CRI 90
LUMINAIRE POWER 7.2W at 120V
RATED LIFE 60000 hr RL
OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K
LUMEN OUTPUT Delivered: 368 lm (LM-79)
INPUT VOLTAGE 120V to 277V AC, 50/60Hz
DRIVER OUTPUT 180mA, 7.6W max power
DIMMING TRIAC and ELV dimming at 120V AC;
 0-10V dimming, 100% to 1% current output
CONSTRUCTION Plated Steel and Glass
DIFFUSER - White Opal Glass
FINISHES Polished Nickel (-20), Oiled Bronze (-22),
 Satin Nickel (-24), Aged Brass (-40)
MOUNTING 4" Octagonal J-Box*,
 4" Square J-Box* with a single device mud ring
 *Deep J-Box (Required to house driver)
STANDARDS UL Dry/Damp listed, Conforms to UL STD 1598,
 Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS
Dia. Canopy: 5.88"
W. Fixture: 6.00"
H. Fixture: 8.25"
 Supplied with 10 ft braided cord

Order example for standard fixture:
3-670-24 (x- Voltage - xxx-Sequence # - xx-Finish)
 3: 120V to 277V
 Order example for optional color temperatures: **3-670-2724**
 27: 2700K, 35: 3500K, 40: 4000K

