

MIRO Chandelier
3-605-xx

oxygen

FIXTURE TYPE _____ LOCATION _____
PROJECT _____ DATE _____




-24 Satin Nickel



-40 Aged Brass

LIGHT SOURCE	LED Array, 3000K, CRI 90
LUMINAIRE POWER	94W at 120V
RATED LIFE	50000 hr RL
OPTIONAL COLOR TEMPERATURES	3000K
LUMEN OUTPUT	Delivered: 2428 lm (LM-79)
INPUT VOLTAGE	120V AC, 60Hz
DRIVER OUTPUT	720mA, 30.24W max power per driver (3 drivers total - 90.72W total max output)
DIMMING	TRIAC Dimming
CONSTRUCTION	Cold Rolled Steel Housing and Canopy
DIFFUSER	- Clear Bubble Acrylic
FINISHES	Satin Nickel (-24), Aged Brass (-40)
MOUNTING	4" Octagonal J-Box
STANDARDS	ETL Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

Dia. Canopy: 7.875"
W. Fixture: 26.00"
H. Fixture: 28.50"
Supplied with 2-8", 2-12", and 3-16"
stems to customize hanging height

Note: Canopy swivel allows up to a 22° slope

Order example for standard fixture:
3-605-24 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V Only

