

RAZZO Outdoor
3-746-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-16 Brushed Aluminum




-15 Black



-Alternate Mounting Option

LIGHT SOURCE	LED Arrays, 3000K, CRI 90
LUMINAIRE POWER	8W at 120V
RATED LIFE	50000 hr RL
OPTIONAL COLOR TEMPERATURES	3000K Only
LUMEN OUTPUT	Delivered: 680 lm (LM-79)
INPUT VOLTAGE	100V to 277V AC, 50/60Hz
DRIVER OUTPUT	200mA, 7.2W max power
DIMMING	Non-dimmable
CONSTRUCTION	Cast Aluminum Housing
DIFFUSER	- Clear Glass
FINISHES	Black (-15), Brushed Aluminum (-16)
MOUNTING	4" Octagonal J-Box (Installer must provide a bead of caulk between fixture housing and mounting surface)
STANDARDS	ETL Wet listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W:	5.125"
H:	6.25"
Ext:	4.25"
M.C:	3.125" From top of fixture

Order example for standard fixture:
3-746-16 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V to 277V

