

TITAN Outdoor

3-708-xx

oxygen

FIXTURE TYPE _____


LOCATION _____

PROJECT _____

DATE _____




-15 Black



-16 Brushed Aluminum

LIGHT SOURCE	1 x 6W LED with Driver on board, 3000K, CRI 90
LUMINAIRE POWER	6.1W at 120V
RATED LIFE	50000 hr RL
OPTIONAL COLOR TEMPERATURES	3000K Only
LUMEN OUTPUT	Delivered: 236 lm (LM-79)
INPUT VOLTAGE	120V AC, 50/60Hz
DRIVER OUTPUT	N/A
DIMMING	TRIAC Dimming
CONSTRUCTION	Cast Aluminum Housing
DIFFUSER	- Etched White Glass
FINISHES	Black (-15), Brushed Aluminum (-16)
MOUNTING	4" Octagonal J-Box (Installer must provide a bead of caulk between fixture housing and mounting surface)
STANDARDS	ETL Wet listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W:	4.75"
H:	4.75"
Ext:	4.00"
M.C:	2.375" From top of fixture

Order example for standard fixture:

3-708-16 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V Only

