

UNO Outdoor
3-700-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-16 Gray



-22 Oiled Bronze

LIGHT SOURCE 1 x 10.1W LED, 3000K, CRI 90

LUMINAIRE POWER 12.4W at 120V

RATED LIFE 60000 hr RL

OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K

LUMEN OUTPUT Delivered: 308 lm (LM-79)

INPUT VOLTAGE 120V to 277V AC, 50/60Hz

DRIVER OUTPUT 350mA, 14.7W max power

DIMMING TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output



CONSTRUCTION Cast Aluminum and Glass

DIFFUSER - Frosted Glass

FINISHES Gray (-16), Oiled Bronze (-22)

MOUNTING 4" Octagonal J-Box
(Installer must provide a bead of caulk between fixture housing and mounting surface)

STANDARDS UL Wet listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W: 5.25"
H: 9.25"
Ext: 4.00"
M.C: 6.10" From top of fixture

Order example for standard fixture:
3-700-22 (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V to 277V
Order example for optional color temperatures: **3-700-2722**
27: 2700K, 35: 3500K, 40: 4000K

