

VELA Wall Sconce
3-527-xx

oxygen

FIXTURE TYPE _____


LOCATION _____

PROJECT _____

DATE _____



-20 Polished Nickel



-22 Oiled Bronze




-24 Satin Nickel



Alternative Position

LIGHT SOURCE	2 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER	24.0W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 408 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	700mA, 29.4W max power
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
CONSTRUCTION	Plated Steel and Acrylic
DIFFUSER	- Matte White Acrylic
FINISHES	Polished Nickel (-20), Oiled Bronze (-22), Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box*, 4" Square J-Box* *Deep J-Box (Required to house driver)
STANDARDS	UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W:	6.875"
H:	12.00"
Ext:	4.00"
M.C:	8.25" From top of fixture

Order example for standard fixture:

3-527-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V to 277V

Order example for optional color temperatures: **3-527-2724**

27: 2700K, 35: 3500K, 40: 4000K

