

**ZENITH Wall Sconce**  
**3-556-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel



-14 Polished Chrome





-22 Oiled Bronze



-40 Aged Brass

- LIGHT SOURCE** 1 x 12.2W LED, 3000K, CRI 90
- LUMINAIRE POWER** 14.6W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 942 lm (LM-79)
- INPUT VOLTAGE** 120V to 277V AC, 50/60Hz
- DRIVER OUTPUT** 350mA, 14.7W max
- DIMMING** TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output
- CONSTRUCTION** Plated Steel and Acrylic
- DIFFUSER** Matte White Acrylic
- FINISHES** Polished Chrome (-14), Oiled Bronze (-22), Satin Nickel (-24), Aged Brass (-40)
- MOUNTING** 4" Octagonal J-Box\* with optional backplate  
 4"x4" Square J-Box\* with single device mud ring  
 \*Deep J-Box (Required to house driver)
- STANDARDS** ETL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



**DIMENSIONS**  
**W: 3.50"**  
**H: 15.125"**  
**Ext: 3.50"**  
**M.C: 13.00" From Top of Fixture**

Order example for standard fixture:

**3-556-xx** (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **3-556-2724**

**27:** 2700K, **35:** 3500K, **40:** 4000K

