

ONDURE Ceiling Fan
3-114-xx



FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-6 White



-15 Black



-24 Satin Nickel



SPECIFICATIONS 3 ABS Blades / 54" Blade Sweep / 16° Blade-Pitch
 125mm DC Motor
 4" and 6" downrod (Included)
 Optional downrods available for high ceilings
 6 Speeds - Reversible with wall control
 0.34A on high / 0.03A on low
 26W on high / 2W on low
 165 rpm on high / 52 rpm on low
 Wall Control (Included)

INPUT VOLTAGE 120V

ENERGY SPECIFICATIONS Airflow: 6665 CFM
 Electric Energy Consumption: 32 W (Excludes Lights)
 Airflow efficiency: 208 CFM/W
 Note: Measured at high speed

FINISHES White (-6), Black (-15),
 Satin Nickel (-24),

STANDARDS cUL Damp Listed



Blade Sweep

DIMENSIONS

Blade Sweep: 54.00"

Ht.: 12.25"

Ceiling to blades: 10.25"

Note: Measured using 4" downrod

ENERGYGUIDE	
Estimated Yearly Energy Cost \$6	Airflow 4,418 Cubic Feet Per Minute
	• The higher the airflow, the more air the fan will move. • Airflow Efficiency: 225 Cubic Feet Per Minute Per Watt
Cost Range of Similar Models (19" - 84") • Based on 12 cents per kWh and 6.4 hours use per day • Your cost depends on rates and use • Energy Use: 20 Watts	
All estimates based on typical use, excluding lights. fc.gov/energy	

