

TEMPLE Ceiling Fan

3-115-xxx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-15 Black/Weathered Gray ABS Blades



-24 Satin Nickel/Weathered Gray ABS Blades



-640 White/Aged Brass/White ABS Blades


SPECIFICATIONS 3 ABS Blades / 56" Blade Sweep / 13° Blade-Pitch
125mm DC Motor
4" and 6" downrod (Included)
Optional downrods available for high ceilings
6 Speeds - Reversible with wall control
0.37A on high / 0.04A on low
26W on high / 2W on low
150 rpm on high / 50 rpm on low
Wall Control (Included)

INPUT VOLTAGE 120V

ENERGY SPECIFICATIONS Airflow: 6339 CFM
Electric Energy Consumption: 31 W (Excludes Lights)
Airflow efficiency: 204 CFM/W
Note: Measured at high speed

FINISHES Black (-15), Satin Nickel (-24), White/Aged Brass (-640)

STANDARDS cUL Wet listed



Blade Sweep

DIMENSIONS

Blade Sweep: 56.00"

Ht.: 13.00"

Ceiling to blades: 9.50"

Note: Measured using 4" downrod

LIGHT INFORMATION

LUMEN OUTPUT Delivered: 1026 lm (LM-79)

LIGHT SOURCE LED Light 24W, 3000K, 90CRI
Dimmable LED with matte white glass diffuser



ENERGYGUIDE	
Estimated Yearly Energy Cost \$5 Cost Range of Similar Models (19 - 84) • Based on 12 cents per kWh and 6.4 hours use per day • Your cost depends on rates and use • Energy Use: 19 Watts All estimates based on typical use, excluding lights	Airflow 4,340 Cubic Feet Per Minute • The higher the airflow, the more air the fan will move • Airflow Efficiency: 224 Cubic Feet Per Minute Per Watt ftc.gov/energy