


quorum



Windmill 44-in Galvanized Indoor/ Outdoor Ceiling Fan (10-Blade)

194410-9

HEIGHT CHART



FAN HEIGHT

Using 6" Downrod

● Distance of 16.5"

○ Distance of 11.5"

GENERAL SPECS

2 Finishes Available

Lifetime Motor Warranty

Ten Aluminum Blades

44" Blade Sweep

30-Degree Blade Pitch

80" Lead Wire

6" Downrod Included

ETL Damp Listed

MECHANICAL SPECS

DC-125 Motor

6 Speeds-Reversible w/ Wall Control

8 Poles

.39/.29/.20/.13/.11/.05 AMPS on H/M/L

32/22/15/10/7/3 WATTS on H/M/L

100/90/80/70/60/50 RPMS on H/M/L

Wall Control Included w/ 194410-9 only

Light Kit Adaptable

Remote Control Included w/ 194410-86 only

Not Hugger Adaptable

Not Slope Ceiling Kit Adaptable

Maximum 25° Slope with Minimum 18" Downrod

Maximum Length Optional Downrod 48"

ENERGY SPECS

Energy Information at High Speed

Airflow: 2296 Cubic Feet/Minute

Electricity Use: 17 Watts (Excludes Lights)

Airflow Efficiency: 135 Cubic Feet/Minute/Watt

Visit QuorumInternational.com for DOE Energy Guide

REMOTE CONTROL



Included

INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

LIGHT KIT OPTIONS

Additional Light Kit options on page 232

201 Railhead Road, Fort Worth, TX 76106 - Tel. (817) 626-5483 - www.QuorumInternational.com

Please be advised that all information shown here is subject to verification by Quorum. In the event of a discrepancy, we reserve the right to make any corrections necessary.