

Installation Instruction

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation. The model No. on the drawings are representative.
2. Thread the Threaded Nipple to the center hole of Cross Bar, secure the Cross Bar to the Outlet Box by threading the two Outlet Box Screws.
3. Connect the fixture wires to the Outlet Box wires as follows. Connect the White Fixture wire to the White Supply Wire, Connect the Black Fixture Wire to the Black Supply Wire. Make sure all wire Connectors are secure and do not easily pull off with the slight tug. If there is no Green Ground Wire from the Outlet Box, Connect the Fixture Ground Wire to the Cross Bar with the Green Grounding Screw provided.
4. Once all wires are connected, tuck them carefully into Outlet Box. Then raise Wall Plate against wall and tighten with Finial.
5. Secure Threaded Pipe to the bottom of Fitter, slide Plastic Washer, Metal Washer, and Plastic Washer to the Threaded Pipe, put the Crystal Tube and Plastic Washer to the Threaded Pipe, tighten with Finial.
6. Slide Glass Shade onto Fitter, thread Bulb to Socket.
7. Return the power to the Outlet Box and test fixture. Your installation is now complete.

