

# Tile 170 Tall Phase

astro

## General

|                           |                                                     |
|---------------------------|-----------------------------------------------------|
| Location:                 | Interior                                            |
| Class:                    | cULus (Class I)                                     |
| Location Rating:          | Dry                                                 |
| Driver Required:          | Mains 120V                                          |
| Installation Orientation: | Wall Mount - Horizontal                             |
| Fitting Method:           | ½" Stub Mount, 3x2" Switch Box<br>or 4" Octagon Box |
| Main Material:            | Metal - Aluminium                                   |
| Dimensions (mm):          | H: 340 W: 170 D: 65                                 |
| Dimensions (inch):        | H: 13.39 W: 6.69 D: 2.56                            |
| Cut Out Hole (mm/inch):   | -                                                   |
| Recess Depth (mm/inch):   | -                                                   |
| Fire Rating:              | -                                                   |
| Cable Length (mm/inch):   | -                                                   |
| Gross Weight (lb):        | 3.56                                                |
| Ada Compliant:            | Yes                                                 |
| Ic Rating:                | -                                                   |

## Lamp

|                                |                |
|--------------------------------|----------------|
| Light Source:                  | Mid-Power LED  |
| Wattage:                       | 2 x 5.9W       |
| Lamp Included:                 | Yes (Integral) |
| Maximum Lamp Length (mm/inch): | -              |
| Luminous Flux (lm):            | To Be Advised  |
| Colour Temp (K):               | 2700           |
| Cri (Ra):                      | 90             |
| Macadam Ellipse:               | 3-Step         |
| Tilt Adjustable Angle (°):     | -              |
| Rotation Adjustable Angle (°): | -              |
| Average Lifetime (hrs):        | 54000          |
| Beam Angle (°):                | -              |

## Electrical

|                                |                                 |
|--------------------------------|---------------------------------|
| Switched:                      | No                              |
| Dimmable:                      | Yes                             |
| Dimming Method:                | Phase - Leading & Trailing Edge |
| Supply Frequency (Hz):         | 50/60                           |
| Driver/Ballast Voltage (V):    | 120                             |
| Driver Average Lifetime (hrs): | 50000                           |
| Efficacy (lm/W):               | To Be Advised                   |

## Additional Information:

|                          |   |
|--------------------------|---|
| Shade Included:          | - |
| Shade/Diffuser Material: | - |
| Shade/Diffuser Finish:   | - |
| F Mark:                  | - |



Code: 1493007

Finish: Matt White

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

# Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

